



Square Ceiling Diffusers Steel • Louvered Face • Fire Rated • Adjustable

Model TDCA-FR • Square Neck • Horizontal-to-Vertical Adjustable Discharge Pattern







Removing Center Core

- 1. Remove shipping clip.
- 2. Push core sideways aganist spring.
- 3. Hold core securely and allow to drop down.









Accessories (Optional)

Check **v** if provided



Duct Size B	Extended Neck Height
6" x 6"	7 1/2"
9" x 9"	7 1/2"
12" x 12"	9 1/2"
15" x 15"	9 1/2"
18" x 18"	12 1/2"



Other Accessories (Optional)

☐ Fusible Link 165° F (212° F is standard)

Standard Finish: #26 White

General Description

- Model TDCA-FR is a UL Classified Fire Rated Ceiling Diffuser Assembly listed in The Underwriters Laboratories "Fire Resistance Directory."
- The Ceiling Diffuser Assembly has a fire resistance rating of 3 hours or less when installed in accordance with the installation instructions.
- TITUS Model TDCA-FR is a high capacity ceiling diffuser.
- Movable vanes, accessible from the face, adjust the vertical discharge pattern from horizontal to vertical.
- In the horizontal setting, the Model TDCA-FR maintains an unbroken horizontal flow pattern from maximum cfm down to minimum, making it an excellent choice for variable air volume applications.
- Core is removable from the face of the diffuser.
- Model TDCA-FR is extremely flexible, with cores available for 1, 2, 3 or 4-way horizontal flow, in addition to the adjustable vanes.
- · Material is heavy gauge steel.

Adjusting Vertical-to-Horizontal Discharge Pattern

