

## T3SW Sidewall VAV Diffuser

Size	Reading	Inlet Static Pressure			
		.08"	0.12"	0.16"	0.2"
12 X 4	Flow	154	190	216	245
	Throw max/min ft	20.6/10.5	24.0/12.8	27.0/13.5	31.8/16.0
	NC Level	29	33	37	39
14 X 4	Flow	207	247	279	307
	Throw max/min ft	22.6/11.8	28.8/15.4	33.5/16.4	36/16.4
	NC Level	29	33	36	38
16 X 4	Flow	245	292	315	347
	Throw max/min ft	27.5/14.7	29.8/16.4	32.8/16.7	32.8/17.7
	NC Level	29	33	36	39
18 X 4	Flow	275	324	358	406
	Throw max/min ft	26.9/14.4	30.8/17	35/19	37.4/19
	NC Level	29	34	36	39
20 X 4	Flow	279	341	385	440
	Throw max/min ft	27.5/14.4	31.8/17.3	36/19.3	39.3/19.6
	NC Level	30	34	38	40
22 X 4	Flow	315	370	428	464
	Throw max/min ft	28.8/16	32/18.3	36.4/19	40.6/22.6
	NC Level	30	34	38	40
24 X 4	Flow	351	411	464	523
	Throw max/min ft	28.8/15.7	32.8/19.6	39.3/21.6	42.6/23.6
	NC Level	30	33	38	41
26 X 4	Flow	381	461	523	586
	Throw max/min ft	29.2/16	33.1/17	37/20.6	41.3/22.3
	NC Level	30	34	39	41
20 X 6	Flow	421	508	637	709
	Throw max/min ft	28.8/16.4	32.8/19.3	39.3/21.6	42.6/25.6
	NC Level	30	35	39	41
22 X 6	Flow	472	565	654	733
	Throw max/min ft	31.5/16.7	38.3/21	43/23.9	49.2/27.2
	NC Level	31	35	39	41
24 X 6	Flow	550	650	754	826
	Throw max/min ft	32.1/17	36/21.6	42.6/24.6	49.2/28.8
	NC Level	31	35	39	41
26 X 6	Flow	565	697	800	868
	Throw max/min ft	31.8/17	35.7/21.9	44.6/25.6	50.5/29.2
	NC Level	32	35	39	42
28 X 6	Flow	610	745	862	964
	Throw max/min ft	32.8/19.6	42.6/23.6	49.2/28.8	52.5/30.5
	NC Level	32	35	39	42
30 X 6	Flow	697	853	985	1101
	Throw max/min ft	32.8/18.3	36/24.2	49.2/27.8	52.5/30.8
	NC Level	32	35	39	42