

PAS FLUSH FACE / SUPPLY / STEEL / ADJUSTABLE

		Neck Velocity	300	400	500	600	700	800	1000	1200	1400	
		Velocity Pressure	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122	
12 x 12 Module	6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275	
		Total Pressure	0.016	0.028	0.044	0.064	0.087	0.113	0.177	0.255	0.347	
		NC (Noise Criteria)	-	-	-	16	21	25	32	38	43	
		1-Way - Horizontal Throw	1-2-7	2-4-10	2-6-12	4-7-15	5-9-17	6-10-18	8-12-20	10-15-22	11-17-23	
		2-Way - Horizontal Throw	1-2-5	2-4-7	2-4-9	4-5-11	4-6-12	5-7-14	6-9-17	7-11-18	8-12-20	
	6 x 6 Neck	Airflow, cfm	75	100	125	150	175	200	250	300	350	
		Total Pressure	0.017	0.029	0.046	0.066	0.090	0.118	0.184	0.265	0.360	
		NC (Noise Criteria)	-	-	13	19	23	28	35	41	45	
		1-Way - Horizontal Throw	1-2-8	2-4-11	3-6-14	4-8-17	5-10-19	7-11-20	9-14-22	11-17-24	13-19-26	
		2-Way - Horizontal Throw	1-2-6	2-4-8	3-5-10	4-6-12	5-7-14	5-8-16	7-10-19	8-12-21	9-14-22	
	24 x 12 Module	6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275
			Total Pressure	0.016	0.028	0.044	0.064	0.087	0.113	0.177	0.255	0.347
			NC (Noise Criteria)	-	-	-	16	21	25	32	38	43
			1-Way - Horizontal Throw	1-2-7	2-4-10	2-6-12	4-7-15	5-9-17	6-10-18	8-12-20	10-15-22	11-17-23
2-Way - Horizontal Throw			1-2-5	2-4-7	2-4-9	4-5-11	4-6-12	5-7-14	6-9-17	7-11-18	8-12-20	
6 x 6 Neck		Airflow, cfm	75	100	125	150	175	200	250	300	350	
		Total Pressure	0.017	0.029	0.046	0.066	0.090	0.118	0.184	0.265	0.360	
		NC (Noise Criteria)	-	-	13	19	23	28	35	41	45	
		1-Way - Horizontal Throw	1-2-8	2-4-11	3-6-14	4-8-17	5-10-19	7-11-20	9-14-22	11-17-24	13-19-26	
		2-Way - Horizontal Throw	1-2-6	2-4-8	3-5-10	4-6-12	5-7-14	5-8-16	7-10-19	8-12-21	9-14-22	
16 x 16 Module		6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275
			Total Pressure	0.016	0.028	0.044	0.064	0.087	0.113	0.177	0.255	0.347
			NC (Noise Criteria)	-	-	-	16	21	25	32	38	43
			1-Way - Horizontal Throw	1-2-8	2-4-10	3-7-13	4-8-15	6-9-17	7-10-18	9-13-20	10-15-22	12-17-23
	2-Way - Horizontal Throw		1-2-6	2-4-8	3-5-10	4-6-11	4-7-13	5-8-15	6-10-17	8-11-18	9-13-20	
	6 x 6 Neck	Airflow, cfm	75	100	125	150	175	200	250	300	350	
		Total Pressure	0.017	0.029	0.046	0.066	0.090	0.118	0.184	0.265	0.360	
		NC (Noise Criteria)	-	-	13	19	23	28	35	41	45	
		1-Way - Horizontal Throw	1-3-9	2-5-12	3-7-15	5-9-17	7-10-19	8-12-20	10-15-22	12-17-24	14-19-26	
		2-Way - Horizontal Throw	1-3-6	2-4-9	3-5-11	4-6-13	5-8-15	6-9-17	7-11-19	9-13-21	10-15-22	
	8" Dia.	Airflow, cfm	105	140	175	209	244	279	349	419	489	
		Total Pressure	0.018	0.032	0.049	0.071	0.097	0.126	0.197	0.284	0.386	
		NC (Noise Criteria)	-	-	16	22	27	31	38	44	49	
		1-Way - Horizontal Throw	1-3-10	3-6-14	4-9-17	6-10-20	8-12-22	9-14-24	12-17-26	14-20-29	16-22-31	
2-Way - Horizontal Throw		1-3-8	3-5-10	4-6-13	5-8-15	6-9-18	7-10-20	8-13-22	10-15-25	12-18-27		
8 x 8 Neck	Airflow, cfm	133	178	222	267	311	356	444	533	622		
	Total Pressure	0.019	0.034	0.052	0.075	0.103	0.134	0.210	0.302	0.411		
	NC (Noise Criteria)	-	12	19	25	29	34	41	47	51		
	1-Way - Horizontal Throw	2-4-12	3-7-16	5-10-20	7-12-23	9-14-25	10-16-27	13-20-30	16-23-33	18-25-35		
	2-Way - Horizontal Throw	2-4-9	3-6-11	5-7-14	6-9-17	7-10-20	8-11-23	10-14-25	11-17-28	13-20-30		
10" Dia.	Airflow, cfm	164	218	273	327	382	436	545	654	764		
	Total Pressure	0.020	0.036	0.056	0.080	0.109	0.143	0.223	0.321	0.437		
	NC (Noise Criteria)	-	14	21	27	32	36	43	49	54		
	1-Way - Horizontal Throw	2-4-13	3-7-17	5-11-22	7-13-26	10-15-28	12-17-30	15-22-33	17-26-36	20-28-39		
	2-Way - Horizontal Throw	2-4-10	3-6-13	5-8-16	6-10-19	7-11-22	8-13-25	11-16-28	13-19-31	15-22-33		
10" Dia.	3-Way - Horizontal Throw	2-4-8	4-5-11	4-7-13	5-8-16	6-9-19	7-11-21	9-13-23	11-16-25	13-19-27		
	4-Way - Horizontal Throw	1-3-6	3-4-8	3-5-10	4-6-12	5-7-14	5-8-16	7-10-18	8-12-20	10-14-21		

Redefine your comfort zone.™ | www.titus-hvac.com



PERFORMANCE DATA

PAS FLUSH FACE / SUPPLY / STEEL / ADJUSTABLE

		Neck Velocity	300	400	500	600	700	800	1000	1200	1400
		Velocity Pressure	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122
20 x 20 Module	6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275
		Total Pressure	0.016	0.028	0.044	0.064	0.087	0.113	0.177	0.255	0.347
		NC (Noise Criteria)	-	-	-	16	21	25	32	38	43
		1-Way - Horizontal Throw	1-2-8	2-4-10	3-7-13	4-8-15	6-9-17	7-10-18	9-13-20	10-15-22	12-17-23
		2-Way - Horizontal Throw	1-2-6	2-4-8	3-5-10	4-6-11	4-7-13	5-8-15	6-10-17	8-11-18	9-13-20
	6 x 6 Neck	3-Way - Horizontal Throw	1-2-5	2-3-6	3-4-8	3-5-10	4-6-11	4-6-12	5-8-14	6-10-15	8-11-16
		4-Way - Horizontal Throw	1-2-4	2-2-5	2-3-6	2-4-7	3-4-9	3-5-10	4-6-11	5-7-12	6-9-13
		Airflow, cfm	75	100	125	150	175	200	250	300	350
		Total Pressure	0.017	0.029	0.046	0.066	0.090	0.118	0.184	0.265	0.360
		NC (Noise Criteria)	-	-	13	19	23	28	35	41	45
8" Dia.	1-Way - Horizontal Throw	1-3-9	2-5-12	3-7-15	5-9-17	7-10-19	8-12-20	10-15-22	12-17-24	14-19-26	
	2-Way - Horizontal Throw	1-3-6	2-4-9	3-5-11	4-6-13	5-8-15	6-9-17	7-11-19	9-13-21	10-15-22	
	3-Way - Horizontal Throw	1-3-5	2-4-7	3-5-9	4-5-11	4-6-13	5-7-14	6-9-16	7-11-17	9-13-19	
	4-Way - Horizontal Throw	1-2-4	2-3-6	2-3-7	3-4-8	3-5-10	4-6-11	5-7-12	6-8-13	7-10-15	
	Airflow, cfm	105	140	175	209	244	279	349	419	489	
8 x 8 Neck	Total Pressure	0.018	0.032	0.049	0.071	0.097	0.126	0.197	0.284	0.386	
	NC (Noise Criteria)	-	-	16	22	27	31	38	44	49	
	1-Way - Horizontal Throw	1-3-10	3-6-14	4-9-17	6-10-20	8-12-22	9-14-24	12-17-26	14-20-29	16-22-31	
	2-Way - Horizontal Throw	1-3-8	3-5-10	4-6-13	5-8-15	6-9-18	7-10-20	8-13-22	10-15-25	12-18-27	
	3-Way - Horizontal Throw	2-3-6	3-4-9	4-5-11	4-6-13	5-8-15	6-9-17	7-11-18	9-13-20	10-15-22	
10" Dia.	4-Way - Horizontal Throw	1-2-5	2-3-7	3-4-8	3-5-10	4-6-12	4-7-13	5-8-15	7-10-16	8-12-17	
	Airflow, cfm	133	178	222	267	311	356	444	533	622	
	Total Pressure	0.019	0.034	0.052	0.075	0.103	0.134	0.210	0.302	0.411	
	NC (Noise Criteria)	-	12	19	25	29	34	41	47	51	
	1-Way - Horizontal Throw	2-4-12	3-7-16	5-10-20	7-12-23	9-14-25	10-16-27	13-20-30	16-23-33	18-25-35	
10 x 10 Neck	2-Way - Horizontal Throw	2-4-9	3-6-11	5-7-14	6-9-17	7-10-20	8-11-23	10-14-25	11-17-28	13-20-30	
	3-Way - Horizontal Throw	2-4-7	3-5-10	4-6-12	5-7-15	6-9-17	6-10-19	8-12-21	10-15-23	11-17-25	
	4-Way - Horizontal Throw	1-3-6	2-4-7	3-5-9	4-6-11	4-7-13	5-7-15	6-9-16	7-11-18	9-13-19	
	Airflow, cfm	164	218	273	327	382	436	545	654	764	
	Total Pressure	0.020	0.036	0.056	0.080	0.109	0.143	0.223	0.321	0.437	
12" Dia.	NC (Noise Criteria)	-	14	21	27	32	36	43	49	54	
	1-Way - Horizontal Throw	2-4-13	3-7-17	5-11-22	7-13-26	10-15-28	12-17-30	15-22-33	17-26-36	20-28-39	
	2-Way - Horizontal Throw	2-4-10	3-6-13	5-8-16	6-10-19	7-11-22	8-13-25	11-16-28	13-19-31	15-22-33	
	3-Way - Horizontal Throw	2-4-8	4-5-11	4-7-13	5-8-16	6-9-19	7-11-21	9-13-23	11-16-25	13-19-27	
	4-Way - Horizontal Throw	1-3-6	3-4-8	3-5-10	4-6-12	5-7-14	5-8-16	7-10-18	8-12-20	10-14-21	
14" Dia.	Airflow, cfm	208	278	347	417	486	556	694	833	972	
	Total Pressure	0.022	0.039	0.061	0.087	0.119	0.155	0.243	0.349	0.476	
	NC (Noise Criteria)	-	16	23	29	34	38	45	51	56	
	1-Way - Horizontal Throw	2-5-15	4-8-20	6-12-25	8-15-29	11-17-31	13-20-33	16-25-37	20-29-41	23-31-44	
	2-Way - Horizontal Throw	2-5-11	4-7-14	6-9-18	7-11-21	8-13-25	10-14-28	12-18-32	14-21-35	17-25-37	
12" Dia.	3-Way - Horizontal Throw	2-5-9	4-6-12	5-8-15	6-9-18	7-11-21	8-12-23	10-15-26	12-18-29	14-21-31	
	4-Way - Horizontal Throw	2-3-7	3-5-9	4-6-12	5-7-14	5-8-16	6-9-18	8-12-20	9-14-22	11-16-24	
	Airflow, cfm	236	314	393	471	550	628	785	942	1100	
	Total Pressure	0.032	0.057	0.089	0.128	0.174	0.227	0.355	0.510	0.695	
	NC (Noise Criteria)	-	18	25	30	35	40	47	52	57	
14" Dia.	1-Way - Horizontal Throw	7-12-22	10-16-25	13-19-28	16-22-31	18-23-33	20-25-35	23-28-40	25-31-43	27-33-47	
	2-Way - Horizontal Throw	6-8-17	8-11-21	9-14-24	11-17-26	13-20-28	15-21-30	19-24-34	21-26-37	23-28-40	
	3-Way - Horizontal Throw	5-7-14	6-10-18	8-12-20	10-14-21	11-16-23	13-18-25	16-20-28	18-21-30	19-23-33	
	4-Way - Horizontal Throw	4-6-11	5-7-14	6-9-15	7-11-17	9-13-18	10-14-19	12-15-22	14-17-24	15-18-26	
	Airflow, cfm	321	428	535	641	748	855	1069	1283	1497	
14" Dia.	Total Pressure	0.034	0.060	0.093	0.135	0.183	0.239	0.374	0.538	0.733	
	NC (Noise Criteria)	12	21	28	34	38	43	50	56	60	
	1-Way - Horizontal Throw	8-14-25	12-18-29	15-23-33	18-25-36	21-27-39	24-29-41	27-33-46	29-36-51	32-39-55	
	2-Way - Horizontal Throw	7-10-20	9-13-25	11-17-28	13-20-30	15-23-33	18-25-35	22-28-39	25-30-43	27-33-47	
	3-Way - Horizontal Throw	6-8-17	7-11-20	9-14-23	11-17-25	13-19-27	15-20-29	19-23-32	20-25-35	22-27-38	
14" Dia.	4-Way - Horizontal Throw	4-6-13	6-9-16	7-11-18	9-13-20	10-15-21	11-16-23	14-18-25	16-20-28	17-21-30	



PAS FLUSH FACE / SUPPLY / STEEL / ADJUSTABLE

		300	400	500	600	700	800	1000	1200	1400	
24 x 24 Mmodule	6" Dia.	Neck Velocity	300	400	500	600	700	800	1000	1200	1400
		Velocity Pressure	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122
	6 x 6 Neck	Airflow, cfm	59	79	98	118	137	157	196	236	275
		Total Pressure	0.016	0.028	0.044	0.064	0.087	0.113	0.177	0.255	0.347
		NC (Noise Criteria)	-	-	-	16	21	25	32	38	43
		1-Way - Horizontal Throw	1-2-8	2-4-10	3-7-13	4-8-15	6-9-17	7-10-18	9-13-20	10-15-22	12-17-23
		2-Way - Horizontal Throw	1-2-6	2-4-8	3-5-10	4-6-11	4-7-13	5-8-15	6-10-17	8-11-18	9-13-20
		3-Way - Horizontal Throw	1-2-5	2-3-6	3-4-8	3-5-10	4-6-11	4-6-12	5-8-14	6-10-15	8-11-16
		4-Way - Horizontal Throw	1-2-4	2-2-5	2-3-6	2-4-7	3-4-9	3-5-10	4-6-11	5-7-12	6-9-13
	8" Dia.	Airflow, cfm	75	100	125	150	175	200	250	300	350
		Total Pressure	0.017	0.029	0.046	0.066	0.090	0.118	0.184	0.265	0.360
		NC (Noise Criteria)	-	-	13	19	23	28	35	41	45
		1-Way - Horizontal Throw	1-3-9	2-5-12	3-7-15	5-9-17	7-10-19	8-12-20	10-15-22	12-17-24	14-19-26
		2-Way - Horizontal Throw	1-3-6	2-4-9	3-5-11	4-6-13	5-8-15	6-9-17	7-11-19	9-13-21	10-15-22
		3-Way - Horizontal Throw	1-3-5	2-4-7	3-5-9	4-5-11	4-6-13	5-7-14	6-9-16	7-11-17	9-13-19
		4-Way - Horizontal Throw	1-2-4	2-3-6	2-3-7	3-4-8	3-5-10	4-6-11	5-7-12	6-8-13	7-10-15
	8 x 8 Neck	Airflow, cfm	105	140	175	209	244	279	349	419	489
		Total Pressure	0.018	0.032	0.049	0.071	0.097	0.126	0.197	0.284	0.386
		NC (Noise Criteria)	-	-	16	22	27	31	38	44	49
		1-Way - Horizontal Throw	1-3-10	3-6-14	4-9-17	6-10-20	8-12-22	9-14-24	12-17-26	14-20-29	16-22-31
		2-Way - Horizontal Throw	1-3-8	3-5-10	4-6-13	5-8-15	6-9-18	7-10-20	8-13-22	10-15-25	12-18-27
		3-Way - Horizontal Throw	2-3-6	3-4-9	4-5-11	4-6-13	5-8-15	6-9-17	7-11-18	9-13-20	10-15-22
		4-Way - Horizontal Throw	1-2-5	2-3-7	3-4-8	3-5-10	4-6-12	4-7-13	5-8-15	7-10-16	8-12-17
	10" Dia.	Airflow, cfm	133	178	222	267	311	356	444	533	622
Total Pressure		0.019	0.034	0.052	0.075	0.103	0.134	0.210	0.302	0.411	
NC (Noise Criteria)		-	12	19	25	29	34	41	47	51	
1-Way - Horizontal Throw		2-4-12	3-7-16	5-10-20	7-12-23	9-14-25	10-16-27	13-20-30	16-23-33	18-25-35	
2-Way - Horizontal Throw		2-4-9	3-6-11	5-7-14	6-9-17	7-10-20	8-11-23	10-14-25	11-17-28	13-20-30	
3-Way - Horizontal Throw		2-4-7	3-5-10	4-6-12	5-7-15	6-9-17	6-10-19	8-12-21	10-15-23	11-17-25	
4-Way - Horizontal Throw		1-3-6	2-4-7	3-5-9	4-6-11	4-7-13	5-7-15	6-9-16	7-11-18	9-13-19	
10 x 10 Neck	Airflow, cfm	164	218	273	327	382	436	545	654	764	
	Total Pressure	0.020	0.036	0.056	0.080	0.109	0.143	0.223	0.321	0.437	
	NC (Noise Criteria)	-	14	21	27	32	36	43	49	54	
	1-Way - Horizontal Throw	2-4-13	3-7-17	5-11-22	7-13-26	10-15-28	12-17-30	15-22-33	17-26-36	20-28-39	
	2-Way - Horizontal Throw	2-4-10	3-6-13	5-8-16	6-10-19	7-11-22	8-13-25	11-16-28	13-19-31	15-22-33	
	3-Way - Horizontal Throw	2-4-8	4-5-11	4-7-13	5-8-16	6-9-19	7-11-21	9-13-23	11-16-25	13-19-27	
	4-Way - Horizontal Throw	1-3-6	3-4-8	3-5-10	4-6-12	5-7-14	5-8-16	7-10-18	8-12-20	10-14-21	
12" Dia.	Airflow, cfm	208	278	347	417	486	556	694	833	972	
	Total Pressure	0.022	0.039	0.061	0.087	0.119	0.155	0.243	0.349	0.476	
	NC (Noise Criteria)	-	16	23	29	34	38	45	51	56	
	1-Way - Horizontal Throw	2-5-15	4-8-20	6-12-25	8-15-29	11-17-31	13-20-33	16-25-37	20-29-41	23-31-44	
	2-Way - Horizontal Throw	2-5-11	4-7-14	6-9-18	7-11-21	8-13-25	10-14-28	12-18-32	14-21-35	17-25-37	
	3-Way - Horizontal Throw	2-5-9	4-6-12	5-8-15	6-9-18	7-11-21	8-12-23	10-15-26	12-18-29	14-21-31	
	4-Way - Horizontal Throw	2-3-7	3-5-9	4-6-12	5-7-14	5-8-16	6-9-18	8-12-20	9-14-22	11-16-24	
12 x 12 Neck	Airflow, cfm	236	314	393	471	550	628	785	942	1100	
	Total Pressure	0.032	0.057	0.089	0.128	0.174	0.227	0.355	0.510	0.695	
	NC (Noise Criteria)	-	18	25	30	35	40	47	52	57	
	1-Way - Horizontal Throw	7-12-22	10-16-25	13-19-28	16-22-31	18-23-33	20-25-35	23-28-40	25-31-43	27-33-47	
	2-Way - Horizontal Throw	6-8-17	8-11-21	9-14-24	11-17-26	13-20-28	15-21-30	19-24-34	21-26-37	23-28-40	
	3-Way - Horizontal Throw	5-7-14	6-10-18	8-12-20	10-14-21	11-16-23	13-18-25	16-20-28	18-21-30	19-23-33	
	4-Way - Horizontal Throw	4-6-11	5-7-14	6-9-15	7-11-17	9-13-18	10-14-19	12-15-22	14-17-24	15-18-26	
14" Dia.	Airflow, cfm	300	400	500	600	700	800	1000	1200	1400	
	Total Pressure	0.033	0.059	0.092	0.133	0.181	0.236	0.369	0.531	0.723	
	NC (Noise Criteria)	-	20	27	33	38	42	49	55	60	
	1-Way - Horizontal Throw	8-13-24	12-18-28	15-22-32	18-24-35	20-26-37	23-28-40	26-32-45	28-35-49	31-37-53	
	2-Way - Horizontal Throw	6-10-19	9-13-24	11-16-27	13-19-29	15-22-32	17-24-34	21-27-38	24-29-42	26-32-45	
	3-Way - Horizontal Throw	5-8-16	7-11-20	9-14-22	11-16-24	13-19-26	14-20-28	18-22-31	20-24-34	21-26-37	
	4-Way - Horizontal Throw	4-6-12	6-8-16	7-10-17	8-12-19	10-15-21	11-16-22	14-17-25	16-19-27	17-21-29	
16" Dia.	Airflow, cfm	321	428	535	641	748	855	1069	1283	1497	
	Total Pressure	0.034	0.060	0.093	0.135	0.183	0.239	0.374	0.538	0.733	
	NC (Noise Criteria)	12	21	28	34	38	43	50	56	60	
	1-Way - Horizontal Throw	8-14-25	12-18-29	15-23-33	18-25-36	21-27-39	24-29-41	27-33-46	29-36-51	32-39-55	
	2-Way - Horizontal Throw	7-10-20	9-13-25	11-17-28	13-20-30	15-23-33	18-25-35	22-28-39	25-30-43	27-33-47	
	3-Way - Horizontal Throw	6-8-17	7-11-20	9-14-23	11-17-25	13-19-27	15-20-29	19-23-32	20-25-35	22-27-38	
	4-Way - Horizontal Throw	4-6-13	6-9-16	7-11-18	9-13-20	10-15-21	11-16-23	14-18-25	16-20-28	17-21-30	

Redefine your comfort zone.™ | www.titus-hvac.com



PERFORMANCE DATA

PDS DROP FACE / SUPPLY / STEEL / ADJUSTABLE

		Neck Velocity	300	400	500	600	700	800	1000	1200	1400	
		Velocity Pressure	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122	
12 x 12 Module	6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275	
		Total Pressure	0.014	0.025	0.039	0.056	0.077	0.100	0.157	0.226	0.307	
		NC (Noise Criteria)	-	-	-	13	18	22	30	35	40	
		1-Way - Horizontal Throw	1-2-7	2-4-10	2-6-12	4-7-13	5-9-14	6-10-15	8-12-17	10-13-19	11-14-20	
		2-Way - Horizontal Throw	1-2-5	2-4-7	2-4-9	4-5-11	4-6-12	5-7-13	6-9-15	7-11-16	8-12-18	
	6 x 6 Neck	Airflow, cfm	75	100	125	150	175	200	250	300	350	
		Total Pressure	0.015	0.026	0.041	0.059	0.080	0.105	0.164	0.236	0.321	
		NC (Noise Criteria)	-	-	-	16	21	25	32	38	43	
		1-Way - Horizontal Throw	1-2-8	2-4-11	3-6-14	4-8-15	5-10-16	7-11-17	9-14-19	11-15-21	13-16-23	
		2-Way - Horizontal Throw	1-2-6	2-4-8	3-5-10	4-6-12	5-7-14	5-8-15	7-10-17	8-12-19	9-14-20	
	24 x 12 Module	6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275
			Total Pressure	0.014	0.025	0.039	0.056	0.077	0.100	0.157	0.226	0.307
			NC (Noise Criteria)	-	-	-	13	18	22	30	35	40
			1-Way - Horizontal Throw	1-2-7	2-4-10	2-6-12	4-7-13	5-9-14	6-10-15	8-12-17	10-13-19	11-14-20
2-Way - Horizontal Throw			1-2-5	2-4-7	2-4-9	4-5-11	4-6-12	5-7-13	6-9-15	7-11-16	8-12-18	
6 x 6 Neck		Airflow, cfm	75	100	125	150	175	200	250	300	350	
		Total Pressure	0.015	0.026	0.041	0.059	0.080	0.105	0.164	0.236	0.321	
		NC (Noise Criteria)	-	-	-	16	21	25	32	38	43	
		1-Way - Horizontal Throw	1-2-8	2-4-11	3-6-14	4-8-15	5-10-16	7-11-17	9-14-19	11-15-21	13-16-23	
		2-Way - Horizontal Throw	1-2-6	2-4-8	3-5-10	4-6-12	5-7-14	5-8-15	7-10-17	8-12-19	9-14-20	
16 x 16 Module		6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275
			Total Pressure	0.014	0.025	0.039	0.056	0.077	0.100	0.157	0.226	0.307
			NC (Noise Criteria)	-	-	-	13	18	22	30	35	40
			1-Way - Horizontal Throw	1-2-8	2-4-10	3-7-12	4-8-13	6-9-14	7-10-15	9-12-17	10-13-19	12-14-20
	2-Way - Horizontal Throw		1-2-6	2-4-8	3-5-10	4-6-11	4-7-13	5-8-13	6-10-15	8-11-16	9-13-18	
	6 x 6 Neck	Airflow, cfm	75	100	125	150	175	200	250	300	350	
		Total Pressure	0.015	0.026	0.041	0.059	0.080	0.105	0.164	0.236	0.321	
		NC (Noise Criteria)	-	-	-	16	21	25	32	38	43	
		1-Way - Horizontal Throw	1-3-9	2-5-12	3-7-14	5-9-15	7-10-16	8-12-17	10-14-19	12-15-21	13-16-23	
		2-Way - Horizontal Throw	1-3-6	2-4-9	3-5-11	4-6-13	5-8-14	6-9-15	7-11-17	9-13-19	10-14-20	
	8" Dia.	Airflow, cfm	105	140	175	209	244	279	349	419	489	
		Total Pressure	0.016	0.028	0.044	0.064	0.087	0.113	0.177	0.255	0.347	
		NC (Noise Criteria)	-	-	13	19	24	28	35	41	46	
		1-Way - Horizontal Throw	1-3-10	3-6-14	4-9-16	6-10-18	8-12-19	9-14-20	12-16-23	14-18-25	16-19-27	
2-Way - Horizontal Throw		1-3-8	3-5-10	4-6-13	5-8-15	6-9-17	7-10-18	8-13-20	10-15-22	12-17-24		
8 x 8 Neck	Airflow, cfm	133	178	222	267	311	356	444	533	622		
	Total Pressure	0.017	0.030	0.047	0.068	0.093	0.121	0.190	0.273	0.372		
	NC (Noise Criteria)	-	-	16	22	27	31	38	44	49		
	1-Way - Horizontal Throw	2-4-12	3-7-16	5-10-18	7-12-20	9-14-21	10-16-23	13-18-26	16-20-28	18-21-30		
	2-Way - Horizontal Throw	2-4-9	3-6-11	5-7-14	6-9-17	7-10-19	8-11-20	10-14-23	11-17-25	13-19-27		
10" Dia.	Airflow, cfm	164	218	273	327	382	436	545	654	764		
	Total Pressure	0.018	0.032	0.051	0.073	0.099	0.130	0.203	0.292	0.398		
	NC (Noise Criteria)	-	-	18	24	29	33	40	46	51		
	1-Way - Horizontal Throw	2-4-13	3-7-17	5-11-20	7-13-22	10-15-24	12-17-25	15-20-28	17-22-31	19-24-34		
	2-Way - Horizontal Throw	2-4-10	3-6-13	5-8-16	6-10-19	7-11-21	8-13-22	11-16-25	13-19-27	15-21-30		



PDS DROP FACE / SUPPLY / STEEL / ADJUSTABLE

		300	400	500	600	700	800	1000	1200	1400	
		Neck Velocity	300	400	500	600	700	800	1000	1200	1400
		Velocity Pressure	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122
20 x 20 Module	6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275
		Total Pressure	0.014	0.025	0.039	0.056	0.077	0.100	0.157	0.226	0.307
		NC (Noise Criteria)	-	-	-	13	18	22	30	35	40
		1-Way - Horizontal Throw	1-2-8	2-4-10	3-7-12	4-8-13	6-9-14	7-10-15	9-12-17	10-13-19	12-14-20
		2-Way - Horizontal Throw	1-2-6	2-4-8	3-5-10	4-6-11	4-7-13	5-8-13	6-10-15	8-11-16	9-13-18
	6 x 6 Neck	3-Way - Horizontal Throw	1-2-5	2-3-6	3-4-8	3-5-9	4-6-9	4-6-10	5-8-11	6-9-12	8-9-13
		4-Way - Horizontal Throw	1-2-4	2-2-5	2-3-6	2-4-7	3-4-8	3-5-8	4-6-9	5-7-10	6-8-11
		Airflow, cfm	75	100	125	150	175	200	250	300	350
		Total Pressure	0.015	0.026	0.041	0.059	0.080	0.105	0.164	0.236	0.321
		NC (Noise Criteria)	-	-	-	16	21	25	32	38	43
8" Dia.	1-Way - Horizontal Throw	1-3-9	2-5-12	3-7-14	5-9-15	7-10-16	8-12-17	10-14-19	12-15-21	13-16-23	
	2-Way - Horizontal Throw	1-3-6	2-4-9	3-5-11	4-6-13	5-8-14	6-9-15	7-11-17	9-13-19	10-14-20	
	3-Way - Horizontal Throw	1-3-5	2-4-7	3-5-9	4-5-10	4-6-10	5-7-11	6-9-13	7-10-14	9-10-15	
	4-Way - Horizontal Throw	1-2-4	2-3-6	2-3-7	3-4-8	3-5-9	4-6-9	5-7-10	6-8-11	7-9-12	
	Airflow, cfm	105	140	175	209	244	279	349	419	489	
8 x 8 Neck	Total Pressure	0.016	0.028	0.044	0.064	0.087	0.113	0.177	0.255	0.347	
	NC (Noise Criteria)	-	-	13	19	24	28	35	41	46	
	1-Way - Horizontal Throw	1-3-10	3-6-14	4-9-16	6-10-18	8-12-19	9-14-20	12-16-23	14-18-25	16-19-27	
	2-Way - Horizontal Throw	1-3-8	3-5-10	4-6-13	5-8-15	6-9-17	7-10-18	8-13-20	10-15-22	12-17-24	
	3-Way - Horizontal Throw	2-3-6	3-4-9	4-5-10	4-6-11	5-8-12	6-9-13	7-10-15	9-11-16	10-12-18	
10" Dia.	4-Way - Horizontal Throw	1-2-5	2-3-7	3-4-8	3-5-9	4-6-10	4-7-11	5-8-12	7-9-13	8-10-14	
	Airflow, cfm	133	178	222	267	311	356	444	533	622	
	Total Pressure	0.017	0.030	0.047	0.068	0.093	0.121	0.190	0.273	0.372	
	NC (Noise Criteria)	-	-	16	22	27	31	38	44	49	
	1-Way - Horizontal Throw	2-4-12	3-7-16	5-10-18	7-12-20	9-14-21	10-16-23	13-18-26	16-20-28	18-21-30	
10 x 10 Neck	2-Way - Horizontal Throw	2-4-9	3-6-11	5-7-14	6-9-17	7-10-19	8-11-20	10-14-23	11-17-25	13-19-27	
	3-Way - Horizontal Throw	2-4-7	3-5-10	4-6-12	5-7-13	6-9-14	6-10-15	8-12-17	10-13-18	11-14-20	
	4-Way - Horizontal Throw	1-3-6	2-4-7	3-5-9	4-6-11	4-7-11	5-7-12	6-9-14	7-11-15	9-11-16	
	Airflow, cfm	164	218	273	327	382	436	545	654	764	
	Total Pressure	0.018	0.032	0.051	0.073	0.099	0.130	0.203	0.292	0.398	
12" Dia.	NC (Noise Criteria)	-	-	18	24	29	33	40	46	51	
	1-Way - Horizontal Throw	2-4-13	3-7-17	5-11-20	7-13-22	10-15-24	12-17-25	15-20-28	17-22-31	19-24-34	
	2-Way - Horizontal Throw	2-4-10	3-6-13	5-8-16	6-10-19	7-11-21	8-13-22	11-16-25	13-19-27	15-21-30	
	3-Way - Horizontal Throw	2-4-8	4-5-11	4-7-13	5-8-14	6-9-15	7-11-17	9-13-18	11-14-20	13-15-22	
	4-Way - Horizontal Throw	1-3-6	3-4-8	3-5-10	4-6-12	5-7-13	5-8-14	7-10-15	8-12-17	10-13-18	
12 x 12 Neck	Airflow, cfm	208	278	347	417	486	556	694	833	972	
	Total Pressure	0.020	0.036	0.056	0.080	0.109	0.143	0.223	0.321	0.437	
	NC (Noise Criteria)	-	13	21	26	31	35	43	48	53	
	1-Way - Horizontal Throw	2-5-15	4-8-20	6-12-23	8-15-25	11-17-27	13-20-29	16-23-32	20-25-35	22-27-38	
	2-Way - Horizontal Throw	2-5-11	4-7-14	6-9-18	7-11-21	8-13-24	10-14-25	12-18-28	14-21-31	17-24-34	
14" Dia.	3-Way - Horizontal Throw	2-5-9	4-6-12	5-8-15	6-9-16	7-11-17	8-12-19	10-15-21	12-16-23	14-17-25	
	4-Way - Horizontal Throw	2-3-7	3-5-9	4-6-12	5-7-13	5-8-14	6-9-15	8-12-17	9-13-19	11-14-20	
	Airflow, cfm	236	314	393	471	550	628	785	942	1100	
	Total Pressure	0.027	0.048	0.076	0.109	0.148	0.194	0.303	0.436	0.593	
	NC (Noise Criteria)	-	15	22	28	33	37	44	50	55	
14 x 14 Neck	1-Way - Horizontal Throw	7-12-19	10-15-22	13-17-24	15-19-26	16-20-29	18-22-30	20-24-34	22-26-37	23-29-40	
	2-Way - Horizontal Throw	6-8-16	8-11-19	9-14-21	11-16-23	13-18-25	15-19-27	17-21-30	19-23-33	21-25-36	
	3-Way - Horizontal Throw	5-7-12	6-10-14	8-11-16	10-12-17	11-13-19	11-14-20	13-16-22	14-17-24	15-19-26	
	4-Way - Horizontal Throw	4-6-10	5-7-12	6-9-13	7-10-14	9-11-15	9-12-16	11-13-18	12-14-20	12-15-22	
	Airflow, cfm	321	428	535	641	748	855	1069	1283	1497	
14 x 14 Neck	Total Pressure	0.029	0.052	0.081	0.116	0.158	0.206	0.322	0.464	0.631	
	NC (Noise Criteria)	-	18	25	31	36	40	47	53	58	
	1-Way - Horizontal Throw	8-14-22	12-18-25	15-20-28	18-22-31	19-24-33	21-25-36	23-28-40	25-31-44	27-33-47	
	2-Way - Horizontal Throw	7-10-19	9-13-22	11-17-25	13-19-27	15-21-29	18-22-31	20-25-35	22-27-38	24-29-42	
	3-Way - Horizontal Throw	6-8-14	7-11-16	9-13-18	11-14-20	13-15-22	13-16-23	15-18-26	16-20-28	18-22-31	
14 x 14 Neck	4-Way - Horizontal Throw	4-6-12	6-9-13	7-11-15	9-12-16	10-13-18	11-13-19	12-15-21	13-16-23	15-18-25	





PDS DROP FACE / SUPPLY / STEEL / ADJUSTABLE

		300	400	500	600	700	800	1000	1200	1400	
		Neck Velocity	300	400	500	600	700	800	1000	1200	1400
		Velocity Pressure	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122
24 x 24 Module	6" Dia.	Airflow, cfm	59	79	98	118	137	157	196	236	275
		Total Pressure	0.014	0.025	0.039	0.056	0.077	0.100	0.157	0.226	0.307
		NC (Noise Criteria)	-	-	-	13	18	22	30	35	40
		1-Way - Horizontal Throw	1-2-8	2-4-10	3-7-12	4-8-13	6-9-14	7-10-15	9-12-17	10-13-19	12-14-20
		2-Way - Horizontal Throw	1-2-6	2-4-8	3-5-10	4-6-11	4-7-13	5-8-13	6-10-15	8-11-16	9-13-18
	3-Way - Horizontal Throw	1-2-5	2-3-6	3-4-8	3-5-9	4-6-9	4-6-10	5-8-11	6-9-12	8-9-13	
	4-Way - Horizontal Throw	1-2-4	2-2-5	2-3-6	2-4-7	3-4-8	3-5-8	4-6-9	5-7-10	6-8-11	
	6 x 6 Neck	Airflow, cfm	75	100	125	150	175	200	250	300	350
		Total Pressure	0.015	0.026	0.041	0.059	0.080	0.105	0.164	0.236	0.321
		NC (Noise Criteria)	-	-	-	16	21	25	32	38	43
1-Way - Horizontal Throw		1-3-9	2-5-12	3-7-14	5-9-15	7-10-16	8-12-17	10-14-19	12-15-21	13-16-23	
2-Way - Horizontal Throw		1-3-6	2-4-9	3-5-11	4-6-13	5-8-14	6-9-15	7-11-17	9-13-19	10-14-20	
8" Dia.	Airflow, cfm	105	140	175	209	244	279	349	419	489	
	Total Pressure	0.016	0.028	0.044	0.064	0.087	0.113	0.177	0.255	0.347	
	NC (Noise Criteria)	-	-	13	19	24	28	35	41	46	
	1-Way - Horizontal Throw	1-3-10	3-6-14	4-9-16	6-10-18	8-12-19	9-14-20	12-16-23	14-18-25	16-19-27	
	2-Way - Horizontal Throw	1-3-8	3-5-10	4-6-13	5-8-15	6-9-17	7-10-18	8-13-20	10-15-22	12-17-24	
8 x 8 Neck	Airflow, cfm	133	178	222	267	311	356	444	533	622	
	Total Pressure	0.017	0.030	0.047	0.068	0.093	0.121	0.190	0.273	0.372	
	NC (Noise Criteria)	-	-	16	22	27	31	38	44	49	
	1-Way - Horizontal Throw	2-4-12	3-7-16	5-10-18	7-12-20	9-14-21	10-16-23	13-18-26	16-20-28	18-21-30	
	2-Way - Horizontal Throw	2-4-9	3-6-11	5-7-14	6-9-17	7-10-19	8-11-20	10-14-23	11-17-25	13-19-27	
10" Dia.	Airflow, cfm	164	218	273	327	382	436	545	654	764	
	Total Pressure	0.018	0.032	0.051	0.073	0.099	0.130	0.203	0.292	0.398	
	NC (Noise Criteria)	-	-	18	24	29	33	40	46	51	
	1-Way - Horizontal Throw	2-4-13	3-7-17	5-11-20	7-13-22	10-15-24	12-17-25	15-20-28	17-22-31	19-24-34	
	2-Way - Horizontal Throw	2-4-10	3-6-13	5-8-16	6-10-19	7-11-21	8-13-22	11-16-25	13-19-27	15-21-30	
10 x 10 Neck	Airflow, cfm	208	278	347	417	486	556	694	833	972	
	Total Pressure	0.020	0.036	0.056	0.080	0.109	0.143	0.223	0.321	0.437	
	NC (Noise Criteria)	-	13	21	26	31	35	43	48	53	
	1-Way - Horizontal Throw	2-5-15	4-8-20	6-12-23	8-15-25	11-17-27	13-20-29	16-23-32	20-25-35	22-27-38	
	2-Way - Horizontal Throw	2-5-11	4-7-14	6-9-18	7-11-21	8-13-24	10-14-25	12-18-28	14-21-31	17-24-34	
12" Dia.	Airflow, cfm	236	314	393	471	550	628	785	942	1100	
	Total Pressure	0.027	0.048	0.076	0.109	0.148	0.194	0.303	0.436	0.593	
	NC (Noise Criteria)	-	15	22	28	33	37	44	50	55	
	1-Way - Horizontal Throw	7-12-19	10-15-22	13-17-24	15-19-26	16-20-29	18-22-30	20-24-34	22-26-37	23-29-40	
	2-Way - Horizontal Throw	6-8-16	8-11-19	9-14-21	11-16-23	13-18-25	15-19-27	17-21-30	19-23-33	21-25-36	
12 x 12 Neck	Airflow, cfm	300	400	500	600	700	800	1000	1200	1400	
	Total Pressure	0.029	0.051	0.079	0.114	0.156	0.203	0.317	0.457	0.622	
	NC (Noise Criteria)	-	17	24	30	35	39	46	52	57	
	1-Way - Horizontal Throw	8-13-21	12-17-24	15-19-27	17-21-30	19-23-32	20-24-34	22-27-38	24-30-42	26-32-46	
	2-Way - Horizontal Throw	6-10-19	9-13-21	11-16-24	13-19-26	15-20-28	17-21-30	20-24-34	21-26-37	23-28-40	
14" Dia.	Airflow, cfm	321	428	535	641	748	855	1069	1283	1497	
	Total Pressure	0.029	0.052	0.081	0.116	0.158	0.206	0.322	0.464	0.631	
	NC (Noise Criteria)	-	18	25	31	36	40	47	53	58	
	1-Way - Horizontal Throw	8-14-22	12-18-25	15-20-28	18-22-31	19-24-33	21-25-36	23-28-40	25-31-44	27-33-47	
	2-Way - Horizontal Throw	7-10-19	9-13-22	11-17-25	13-19-27	15-21-29	18-22-31	20-25-35	22-27-38	24-29-42	
16" Dia.	Airflow, cfm	419	559	698	838	977	1117	1396	1676	1955	
	Total Pressure	0.031	0.055	0.086	0.124	0.169	0.220	0.344	0.496	0.675	
	NC (Noise Criteria)	12	21	28	34	38	43	50	56	60	
	1-Way - Horizontal Throw	10-16-25	14-20-29	17-23-32	20-25-35	22-27-38	23-29-41	26-32-45	29-35-50	31-38-54	
	2-Way - Horizontal Throw	8-11-22	10-15-25	13-19-28	15-22-31	18-24-34	20-25-36	23-28-40	25-31-44	27-34-48	
3-Way - Horizontal Throw	6-10-16	9-13-19	11-15-21	13-16-23	14-18-25	15-19-26	17-21-30	19-23-32	20-25-35		
4-Way - Horizontal Throw	5-7-13	7-10-15	8-12-17	10-13-19	11-14-20	13-15-22	14-17-24	15-19-27	17-20-29		



- Data obtained from tests conducted in accordance with ANSI / ASHRAE Standard 70-2006. Actual performance, with flexible duct inlet, may vary in the field. See the Engineering Guidelines section of this catalog for additional information.
- Throw values given are for terminal velocities of 150, 100 and 50 fpm and for isothermal conditions
- For an explanation of catalog throw data, see the section, Engineering Guidelines
- NC values based on octave band 2 to 7 sound power levels minus a room absorption of 10 dB
- Each NC value represents the noise criteria curve that will not be exceeded by the sound pressure in any of the octave bands, 2 through 7, with a room absorption of 10 dB, re 10<sup>-12</sup> watts
- Dash (-) in space denotes an NC value of less than 10
- All pressures are given in inches of water
- To obtain static pressure, subtract the velocity pressure from the total pressure

PAR, PXP, PMR, PXP-DR, PDR PERFORMANCE DATA

PAR, PXP, PMR - FLUSH FACE - RETURN; PXP-DR, PDR - DROP FACE - RETURN

	Neck Size	Neck Vel, fpm	300	400	500	600	700	800	1000	1200	1400
		Vp, in. Wg	0.01	0.01	0.02	0.02	0.03	0.04	0.06	0.09	0.12
		Ps (-), in. Wg	0.03	0.06	0.09	0.13	0.17	0.23	0.36	0.51	0.70
12 x 12 Face	6 Dia. *	Flow Rate, cfm	59	78	98	118	137	157	196	235	275
		Room NC	-	-	-	14	18	21	27	32	36
	6 x 6 Neck *	Flow Rate, cfm	75	100	125	150	175	200	250	300	350
		Room NC	-	-	12	17	21	24	30	35	39
	10 x 10 Neck	Flow Rate, cfm	208	278	347	417	486	556	694	833	972
		Room NC	15	23	29	33	37	41	47	51	55
24 x 24 Face	Neck Size	Neck Vel, fpm	300	400	500	600	700	800	1000	1200	1400
		Vp, in. Wg	0.01	0.01	0.02	0.02	0.03	0.04	0.06	0.09	0.12
		Ps (-), in. Wg	0.03	0.06	0.09	0.13	0.18	0.24	0.37	0.54	0.73
	6 Dia. *	Flow Rate, cfm	59	78	98	118	137	157	196	235	275
		Room NC	-	-	-	13	17	20	26	31	34
	6 x 6 Neck *	Flow Rate, cfm	75	100	125	150	175	200	250	300	350
		Room NC	-	-	-	14	18	21	27	32	35
	8 Dia. *	Flow Rate, cfm	105	140	174	209	244	279	349	419	488
		Room NC	-	-	13	17	21	24	30	35	38
	8 x 8 Neck *	Flow Rate, cfm	133	178	222	267	311	356	444	533	622
		Room NC	-	-	14	18	22	25	31	36	39
	10 Dia. *	Flow Rate, cfm	164	218	273	327	382	436	545	654	763
		Room NC	-	-	16	20	24	27	33	38	41
	10 x 10 Neck *	Flow Rate, cfm	208	278	347	417	486	556	694	833	972
		Room NC	-	11	17	21	25	28	34	39	42
	12 Dia. *	Flow Rate, cfm	235	314	392	471	549	628	785	942	1099
		Room NC	-	12	17	22	26	29	34	39	43
	12 x 12 Neck *	Flow Rate, cfm	300	400	500	600	700	800	1000	1200	1400
		Room NC	-	14	20	24	28	31	37	42	45
	14 Dia. *	Flow Rate, cfm	320	427	534	641	748	855	1068	1282	1495
		Room NC	-	15	21	25	29	32	38	43	46
	15 x 15 Neck *	Flow Rate, cfm	469	625	781	938	1094	1250	1563	1875	2188
		Room NC	-	16	22	26	30	33	39	44	47
	16 Dia. *	Flow Rate, cfm	419	558	698	837	977	1116	1395	1674	1953
Room NC		11	18	24	28	32	35	41	46	49	
18 x 18 Neck *	Flow Rate, cfm	675	900	1125	1350	1575	1800	2250	2700	3150	
	Room NC	11	18	24	28	32	36	41	46	49	
22 x 22 Neck	Flow Rate, cfm	1008	1344	1681	2017	2353	2689	3361	4033	4706	
	Room NC	13	20	26	30	34	37	43	47	51	
Other Sizes	Neck Size	Neck Vel, fpm	300	400	500	600	700	800	1000	1200	1400
		Vp, in. Wg	0.01	0.01	0.02	0.02	0.03	0.04	0.06	0.09	0.12
		Ps (-), in. Wg	0.03	0.06	0.09	0.13	0.17	0.23	0.36	0.51	0.70
	10 x 22 (12 x 24 Face)	Flow Rate, cfm	458	611	764	917	1069	1222	1528	1833	2139
		Room NC	-	-	-	14	18	21	27	32	36
	14 x 14 (16 x 16 Face)	Flow Rate, cfm	408	544	681	817	953	1089	1361	1633	1906
		Room NC	-	-	12	17	21	24	30	35	39
	18 x 18 (20 x 20 Face)	Flow Rate, cfm	675	900	1125	1350	1575	1800	2250	2700	3150
		Room NC	-	11	17	22	26	29	35	40	44
	22 x 46 (24 x 48 Face)	Flow Rate, cfm	2108	2811	3514	4217	4919	5622	7028	8433	9839
Room NC		12	20	25	30	34	38	43	48	52	

PAR, PXP, PMR, PXP-DR, PDR PERFORMANCE NOTES

- Supply unit with deflectors removed
- Static pressures are negative, in inches of water, measured per ANSI/ASHRAE Standard 70-2006
- Noise Criteria (NC) based on a room absorption of 10 dB, re 10<sup>-12</sup> watts, measured per ANSI/ASHRAE Standard 70-2006
- These products have been tested per ANSI/ASHRAE Standard 70-2006. Actual performance, with flexible duct inlet, may vary in the field.
- See the section, Engineering Guidelines for additional information