


Submittal

TLFR 05-22-19

Laminar Flow Ceiling Diffusers Perforated Face

Model: TLFR-AA • Removable Face • Aluminum
TLFR-SS • Removable Face • Stainless Steel



General Description

- Model TLFR laminar flow diffuser generates a low velocity, evenly distributed, unidirectional air pattern.
- Introduces clean supply air to the space with minimal entrainment of room air, occurring at the boundaries of the supply air mass of a diffuser or array of diffusers.
- Airtight plenum/filter housing construction
- Integral filter rack for use with high efficiency gel seal type filters

- Quick change tool-less autoaligning filter retention system
- Static Pressure Test Port
- Perforated face is quickly removed by loosening ¼ turn fasteners.
- Snap-in removable equalization baffles
- Retainer cables prevent accidental dropping of perforated face after removal.

- Designed for surfaced mounted or conventional T-bar ceiling system.
- Compatible with 1" or 1½" T-bar ceiling grids.
- Compatible with 2", 3", and 4" thick filters
- Compatible filter models are: HEPA-R, ULPA-R, MERV14-R, & MERV15-R

Basic Unit Configuration -

Check if provided.

Construction Material

Aluminum Construction

304 Stainless Steel Construction

Face Free Area

13% Free Area Perforated Face (For airflows up to 35 CFM/ft²*)

- 22% Free Area Perforated Face (For airflows between 35 & 65 CFM/ft^{2*})
- 33% Free Area Perforated Face (For airflows 65 CFM/ft² and higher*)

Finish

- #01 Aluminum
- #01A Aluminum Antimicrobial
- #04 Mill Finish
- #26 White
 - #26A White Antimicrobial
- #84 Black

Accessories (Optional) - Check frovided.

- Radial Damper Cable Operated
- Butterfly Damper Cable Operated
- Aerosol Injection Port & Distribution Manifold
- MRI Compatible Construction


Removable Equalization Baffle

- Factory Certified Leak Tested -In accordance with IEST-RP-CC034.4
- Fully Welded Plenum & Inlet


HEPALert LED Filter Indicator - 24V

- HEPALert LED Filter Indicator Battery
- Operated
- 1/2" Foil Faced Insulated Plenum (External)


Knife Edge/Gel Seal Detail:



Cable Operated Damper Detail:



Port & Cable Operator Details:



Aerosol Manifold Details:

