


# Square Ceiling Diffusers Steel • Fire Rated • High Performance

Model TMS-FR • Round Neck



## **Accessories (Optional)**

Fire Damper with Extended Neck

Check ✓ if provided


 Round Duct Size B
 Extended Neck Height

 6", 7"
 8"

 8"
 8 1/4"

 10"
 9 5/6"


 12", 14", 15"
 9 3/4"



#### Other Accessories (Optional)

Fusible Link 165°F (212°F is standard).

### Optional Volume Adjustment Damper Control • Removing Center Cone



# Standard Finish: #26 White General Description —

- Model TMS-FR is a UL Classified Fire Rated Ceiling Diffuser Assembly listed in The Underwriters Laboratories "Fire Resistance Directory."
- The Ceiling Diffuser Assembly has a fire resistance rating of 3 hours or less when installed in accordance with the installation instructions.
- Model TMS-FR delivers supply air in a true 360° pattern. Designed to protect ceiling from streaking and smudging associated with many other types of ceiling diffusers.
- Excellent for variable volume systems. The uniform, nearly horizontal jet from the outer cone maintains effective room air distribution even when the air volume varies over a considerable range.
- The TMS-FR consists of 3 concentric cones in all sizes. This uniformity of design enhances appearance in installations where more than one size is involved.
- Adjustment of the optional volume adjustment damper is achieved without removing the inner cone (see above).
- Quick removal of the inner cone with a hex key speeds installation (see above).
- All cones are die-stamped, one-piece construction with smooth, clean surfaces and no corner joints.
- · Material is heavy gauge steel.