



Square Ceiling Diffusers Steel • Louvered Face • Fire Rated • High Capacity

Model TDC-FR • Square Neck




Optional Pattern Check ✓ selection




Removing Center Core

- 1. Remove shipping clip.
- 2. Push core sideways aganist spring.
- 3. Hold core securely and allow to drop down.








Accessories (Optional)

Check if provided



Duct Size B	Extended Neck Height
6" x 6"	7 1/2"
9" x 9"	7 1/2"
12" x 12"	9 1/2"
15" x 15"	9 1/2"
18" x 18"	12 1/2"
21" x 21"	12 1/2"



Other Accessories (Optional)

Fusible Link 165°F (212°F is standard)

Standard Finish: #26 White General Description —

- Model TDC-FR is a UL Classified Fire Rated Ceiling Diffuser Assembly listed in The Underwriters Laboratories "Fire Resistance Directory."
- The Ceiling Diffuser Assembly has a fire resistance rating of 3 hours or less when installed in accordance with the installation instructions.
- TITUS Model TDC-FR is a high capacity ceiling diffuser. Because it maintains an unbroken horizontal flow pattern from maximum cfm down to minimum, it is an excellent choice for variable air volume applications.
- · Core is removable from the face of the diffuser.
- Model TDC-FR is extremely flexible, with cores available for 1, 2, 3 or 4-way horizontal flow patterns.
- · Material is heavy gauge steel.

