


## Plenum Slot Diffuser Fire Rated • Return

Model TBDR-FR • 1 or 2 Slots




Model	Number of Slots	Slot Width S	w	Y
TBDR-FR	1	3/4	2 3/4	1 3/4
TBDR-FR	2	3/4	4 1/2	3 1/2
TBDR-FR	1	1	3	2
TBDR-FR	2	1	4 <sup>15</sup> / <sub>16</sub>	3 15/16
TBDR-FR	1	1 <sup>1</sup> / <sub>2</sub>	3 <sup>1</sup> / <sub>2</sub>	2 1/2
*TBDR-FR	2	1 1/2	6 1/4	5 <sup>1</sup> / <sub>4</sub>

Available Lengths L
24
36
48



## **Accessories (Optional)**

Check ✓ if provided



## Standard Finish:

#84 Black on exposed surfaces. #26 White on center T-bars and optional side T-Bars.

## **General Description**

Model TBDR-FR is a fire rated plenum slot diffuser. The design meets UL time-vs-temperature test criteria, also NFPA 90A requirements.

The fire rated reurn unit has a light baffle to prevent light transmission and line of sight into the ceiling plenum. The TBDR-FR is designed to provide the same efficient return performance as the supply diffuser.

When you specify TITUS Model TBDR-FR diffusers, you get these features:

- Damper with fuse link (212° F).
- For use in 3-hour, or less, fire rated exposed grid, suspended ceilings.
- Choice of  $^3/_4$ ", 1" or  $1^1/_2$ " slot width, 1 or 2 parallel slots\*.
- Available in 24", 36", 48" nominal lengths.
- · Material is steel.
- Must be installed according to installation instructions for UL classification.
- \* Note: The 2-slot, 11/2" slot width diffusers are not UL classified.