



Titus Model	Unit Size	Rated Motor Current (Single-phase, 60hz)**			Motor HP
		120 Volt	208 or 240 V	277 or 480* V	
TFS(F)	A	1.25	0.6	0.54	1/10
	B	2.3	0.9	0.8	1/6
	C	4.0	1.8	1.4	1/4
	D	8.5	3.6	3.0	1/3
	E	8.6	4.2	4.5	3/4
	G	n/a	13.2	9.9	(2) 3/4
TFS(F) w/ECM	B	3	n/a	1.6	1/3 ECM
	C	4.6	n/a	2.1	1/3 ECM
	D	5.6	n/a	2.8	1/2 ECM
	E	9.7	n/a	4.9	3/4 ECM
	G	21.1	n/a	11.8	(2) 1 ECM
TQS	2	4.0	1.8	1.3	1/6
	3	7.0	3.0	2.4	1/4
	4	9.8	4.1	2.9	1/3
	5	10.0	4.3	3.3	1/3
	6	13.4	7.2	5.4	3/4
	7	n/a	9.0	6.5	1
TQS w/ECM	4	7.7	n/a	4.1	1/2 ECM
	6	12.8	n/a	6.9	1 ECM
TQP	2	3.6	1.5	1.3	1/6
	3	5.3	2.6	2.2	1/4
	4	7.8	3.2	2.9	1/3
	5	9.2	3.3	3.2	1/3
	6	12.3	6.3	5.4	3/4
TQP w/ECM	4	6.2	n/a	3.1	1/2 ECM
	6	11.4	n/a	6.5	1 ECM
FLS	2	3.9	1.6	1.2	1/6
	3	5.8	2.4	1.8	1/4
	4	8.2	3.4	2.5	(2) 1/6
FLS w/ECM	3	4.2	n/a	2.3	1/3 ECM
	4	8.5	n/a	5	1/3 ECM
FLP	2	4.3	1.8	1.3	1/6
	4	5.4	2.3	1.7	1/4
LHK	3	5.8	2.5	1.8	1/4
	4	6.4	3.0	2.5	1/3
LHK w/ECM	3	4.1	n/a	2.4	1/3 ECM
	4	3.9	n/a	2.3	1/3 ECM
PFC	10	3.4	1.7	1.7	1/4
	14	7.0	3.1	3.2	1/3
	16	11.4	5.2	5.1	3/4
PFC w/ECM	10	5.0	n/a	2.3	1/3 ECM
	14	4.9	n/a	2.3	1/2 ECM
	16	11.1	n/a	6.0	1 ECM

*480 Volt models use 277 volt motors.

**Three-phase models use single-phase motors.