


Fibre Free

Overview

Fibre Free Liner

Titus offers a wide variety of liners suitable to meet any application requirement. Fibre Free is an engineered polymer foam insulation. Fibre Free contains no fiberglass and has a cleanable surface, making it ideal for many hospital and IAQ applications.



FIBRE FREE

MODELS:

- ½" Fibre Free
- 1" Fibre Free

½" FIBRE FREE

INSULATION CHARACTERISTICS

Material:	EPFI (Engineered Polymer Foam Insulation)
Thickness:	½"
R-Value:	2.0 ft ² °F h/Btu @ 75° F
Density:	1.5 lbs/ft ³
Flame Spread:	less than 25
Smoke Density:	less than 50
Mold Growth:	None

CODE COMPLIANCES

NFPA 90A & 90B	Appliances
NFPA 255	Flame / Smoke Spread (25/50)
UL 181	Air Erosion
UL 181	Mold Growth and Humidity
UL 723	Flame / Smoke Spread (25/50)
ASTM E96	Water Vapor Transmission
ASTM E84	Flame / Smoke Spread (25/50)
Factory Mutual Listed	



See website for Specifications

1" FIBRE FREE

INSULATION CHARACTERISTICS

Material:	EPFI (Engineered Polymer Foam Insulation)
Thickness:	1"
R-Value:	4.0 ft ² °F h/Btu @ 75° F
Density:	1.5 lbs/ft ³
Flame Spread:	less than 25
Smoke Density:	less than 50
Mold Growth:	None

CODE COMPLIANCES

NFPA 90A & 90B	Appliances
NFPA 255	Flame / Smoke Spread (25/50)
UL 181	Air Erosion
UL 181	Mold Growth and Humidity
UL 723	Flame / Smoke Spread (25/50)
ASTM E96	Water Vapor Transmission
ASTM E84	Flame / Smoke Spread (25/50)
Factory Mutual Listed	

