

# TVB Series Design Features

## HIGH PERFORMANCE

The Titus vertical floor mounted fan coil units are designed to maximize flexibility of selection and installation.

The units are also designed to exceed the stringent quality standards of the institutional market, while remaining cost competitive in the light commercial segment of the market.

Titus vertical fan coil units set the new standards for quality, flexibility, and competitive pricing.

#### **DESIGN FLEXIBILITY**

The extensive variety of standard options available on vertical floor fan coil units are where you find the versatility to fit any HVAC system designer's needs. Models TVBF and TVBA allow for additional height and width dimensions to meet architectural demand.

Options include: single wall stainless steel drain pan; MERV 7, MERV 8 and MERV 14 filters; and electric heat with single point power connection. All electric heat units are listed with ETL as an assembly and carry the cETL label.

All units comply with the latest edition of AHRI Standard 440 for testing and rating fan coil units, are certified, and display the AHRI symbol.

High efficiency motors, fan relays, disconnects and fusing mean easier coordination between mechanical and electrical trades.

Coil options allow for three or four row chilled water or DX cooling coils, and one or two row hot water or steam heating coils.

Silent solid state relays are available for fan and electric heat control in sound sensitive environments.

## **CONVENIENT INSTALLATION**

All vertical floor fan coils are shipped completely assembled, reducing field installation time and labor. All units are thoroughly inspected and tested prior to shipment, eliminating potential problems at startup. Motor wiring is brought to a junction box on the inside of the unit end pocket, reducing electrical hook-up time.

Factory furnished valve packages assure proper fit, operation and performance.

For fast track jobs, the vertical floor fan coil is available on Quick Ship with 5, 10 or 15 day lead times.

## OPTIMUM BUILDING PERFORMANCE

Concealed vertical floor fan coil chassis are built from galvanized steel. This metal surpasses the ASTM 125 hour salt spray test for corrosion and rust. Exposed cabinet models are powder coated galvannealed steel.

All units, with or without electric heat, are cETL listed and labeled. All wiring is in compliance with NEC, assuring safety and quality for the owner.

Floor mounted cabinet models feature finned tubular heating elements in the reheat position, protecting room occupants from electrical shock.

Vertical floor fan coil units have a removable fan/drain pan assembly. The entire fan assembly can be easily removed from the unit and serviced on a workbench.

Filters are easily replaceable from the return air toe space without the need for tools or removal of the front panel (TVB only).

