

| ESV | | | | | | | | | |
|------|-----------------|-----------------|------------|----------------|----------------------|-----------------|-----------------|--------------|---------------|
| Size | 22 ga. Base Box | 20 ga. Base Box | Attenuator | Ultraloc Liner | w/Pneumatic Controls | w/DDC or Analog | w/Electric Heat | w/1 Row Coil | w/2 Row Coils |
| 4 | 11 | 15 | +15 | +7 | +4 | +9 | +18 | +5 | +6 |
| 5 | 11 | 15 | +15 | +7 | +4 | +9 | +18 | +5 | +6 |
| 6 | 11 | 15 | +15 | +7 | +4 | +9 | +18 | +5 | +6 |
| 7 | 13 | 16 | +16 | +8 | +4 | +9 | +18 | +5 | +7 |
| 8 | 13 | 16 | +16 | +8 | +4 | +9 | +18 | +5 | +7 |
| 9 | 17 | 20 | +19 | +8 | +4 | +9 | +23 | +7 | +9 |
| 10 | 17 | 20 | +19 | +8 | +4 | +9 | +23 | +7 | +9 |
| 12 | 20 | 24 | +23 | +10 | +4 | +9 | +25 | +9 | +12 |
| 14 | 28 | 30 | +28 | +15 | +4 | +9 | +27 | +10 | +15 |
| 16 | 32 | 34 | +31 | +17 | +4 | +9 | +28 | +12 | +17 |
| 40 | 52 | 55 | +45 | +27 | +4 | +9 | +30 | +17 | +25 |

| EDV | | | | | |
|------|-------------------------------|---|------------------------------------|----------------------|-------|
| Size | 22 ga. Base Box No Attenuator | 22 ga. Attenuator Box w/o Mixing Baffle | 22 ga. Attenuator w/ Mixing Baffle | w/Pneumatic Controls | w/DDC |
| 4 | 38 | 66 | 68 | +8 | +18 |
| 5 | 38 | 66 | 68 | +8 | +18 |
| 6 | 38 | 66 | 68 | +8 | +18 |
| 7 | 42 | 76 | 79 | +8 | +18 |
| 8 | 42 | 76 | 79 | +8 | +18 |
| 9 | 52 | 94 | 98 | +8 | +18 |
| 10 | 52 | 94 | 98 | +8 | +18 |
| 12 | 62 | 116 | 120 | +8 | +18 |
| 14 | 78 | 144 | 148 | +8 | +18 |
| 16 | 86 | 166 | 171 | +8 | +18 |

Note: Weights are approximate. Actual weight may vary based on specific options selected.

| MDV | | | |
|------|-----------------|----------------------|-------|
| Size | 22 ga. Base Box | w/Pneumatic Controls | w/DDC |
| 4 | 72 | +8 | +18 |
| 5 | 72 | +8 | +18 |
| 6 | 72 | +8 | +18 |
| 7 | 84 | +8 | +18 |
| 8 | 84 | +8 | +18 |
| 9 | 104 | +8 | +18 |
| 10 | 104 | +8 | +18 |
| 12 | 128 | +8 | +18 |
| 14 | 158 | +8 | +18 |
| 16 | 183 | +8 | +18 |

| TFS | | | | | | |
|------|---------------------------------|--------------------------|--------------------|-----------------|--------------|--------------|
| Size | 20 ga. Base Box w/Attenuator | w/ Pneumatic Controls | w/DDC or Analog | w/Electric Heat | w/1 Row Coil | w/2 Row Coil |
| A | 120 | +4 | +9 | +23 | +7 | +9 |
| B | 145 | +4 | +9 | +25 | +9 | +12 |
| C | 150 | +4 | +9 | +25 | +9 | +12 |
| D | 220 | +4 | +9 | +30 | +12 | +17 |
| E | 220 | +4 | +9 | +30 | +12 | +17 |
| G | 240 | +4 | +9 | +35 | +13 | +18 |

Note: Weights are approximate. Actual weight may vary based on specific options selected.

TFS - F Phantom

| Size | 20 ga. Base Box w/Attenuator | w/ Pneumatic Controls | w/DDC or Analog | w/Electric Heat | w/1 Row Coil | w/2 Row Coil |
|------|---------------------------------|--------------------------|--------------------|-----------------|--------------|--------------|
| B | 180 | +4 | +9 | +25 | +9 | +12 |
| C | 185 | +4 | +9 | +25 | +9 | +12 |
| D | 260 | +4 | +9 | +30 | +12 | +17 |
| E | 260 | +4 | +9 | +30 | +12 | +17 |

TQS

| Size | 20 ga. Base Box | w/ Pneumatic Controls | w/DDC or Analog | w/Electric Heat | w/1 Row Coil | w/2 Row Coil |
|------|-----------------|--------------------------|--------------------|-----------------|--------------|--------------|
| 2 | 145 | +4 | +9 | +25 | +9 | +12 |
| 3 | 150 | +4 | +9 | +25 | +9 | +12 |
| 4 | 155 | +4 | +9 | +25 | +9 | +12 |
| 5 | 220 | +4 | +9 | +30 | +12 | +17 |
| 6 | 225 | +4 | +9 | +30 | +12 | +17 |
| 7 | 230 | +4 | +9 | +30 | +12 | +17 |

TQP

| Size | 20 ga. Base Box | w/ Pneumatic Controls | w/DDC or Analog | w/Electric Heat | w/1 Row Coil | w/2 Row Coil |
|------|-----------------|--------------------------|--------------------|-----------------|--------------|--------------|
| 2 | 145 | +4 | +9 | +25 | +9 | +12 |
| 3 | 150 | +4 | +9 | +25 | +9 | +12 |
| 4 | 155 | +4 | +9 | +25 | +9 | +12 |
| 5 | 220 | +4 | +9 | +30 | +12 | +17 |
| 6 | 225 | +4 | +9 | +30 | +12 | +17 |

Note: Weights are approximate. Actual weight may vary based on specific options selected.

FLS

| Size | 20 ga. Base Box | w/ Pneumatic Controls | w/DDC or Analog | w/Electric Heat | w/1 Row Coil | w/2 Row Coil |
|------|-----------------|-----------------------|-----------------|-----------------|--------------|--------------|
| 2 | 113 | +4 | +9 | +23 | +10 | +14 |
| 3 | 123 | +4 | +9 | +23 | +10 | +14 |
| 4 | 153 | +4 | +9 | +23 | +10 | +14 |

FLP

| Size | 20 ga. Base Box | w/ Pneumatic Controls | w/DDC or Analog | w/Electric Heat | w/1 Row Coil | w/2 Row Coil |
|------|-----------------|-----------------------|-----------------|-----------------|--------------|--------------|
| 2 | 98 | +4 | +9 | +23 | +10 | +14 |
| 4 | 113 | +4 | +9 | +23 | +10 | +14 |

LHK

| Size | 20 ga. Base Box | w/DDC | w/Electric Heat | w/1 Row Coil | w/2 Row Coil |
|------|-----------------|-------|-----------------|--------------|--------------|
| 3 | 120 | +9 | +23 | +7 | +9 |
| 4 | 128 | +9 | +23 | +7 | +9 |

PFC

| Size | 20 ga. Base Box | w/DDC | w/Electric Heat | w/1 Row Coil | w/2 Row Coil |
|------|-----------------|-------|-----------------|--------------|--------------|
| 10 | 115 | +9 | +23 | +7 | +9 |
| 14 | 120 | +9 | +27 | +10 | +15 |
| 16 | 128 | +9 | +28 | +12 | +17 |

Note: Weights are approximate. Actual weight may vary based on specific options selected.

| QCV | | | |
|------|----------|----------------------|-------|
| Size | Base Box | w/Pneumatic Controls | w/DDC |
| A | 18 | +4 | +9 |
| B | 20 | +4 | +9 |
| C | 22 | +4 | +9 |
| D | 24 | +4 | +9 |
| E | 26 | +4 | +9 |
| F | 28 | +4 | +9 |
| G | 30 | +4 | +9 |
| H | 32 | +4 | +9 |
| J | 34 | +4 | +9 |
| K | 38 | +4 | +9 |
| L | 40 | +4 | +9 |
| M | 41 | +4 | +9 |
| N | 45 | +4 | +9 |
| P | 50 | +4 | +9 |
| R | 55 | +4 | +9 |

Note: Weights are approximate. Actual weight may vary based on specific options selected.