

## Passive Chilled Beam • CBPE • Passive Chilled Beam Diffuser • Exposed Installation

NOMINAL LENGTH (FT)	A (IN)	QTY OF MOUNT BRACKET
2	23 7/8	2
3	35 7/8	2
4	47 7/8	3
5	59 7/8	3
6	71 7/8	3
7	83 7/8	3
8	95 7/8	3
9	107 7/8	4
10	119 7/8	4

NOMINAL WIDTH (IN)	B (IN)
13	12 3/4
17	16 3/4
18	17 3/4
22	21 3/4
24	23 3/4

NOMINAL HEIGHT (IN)	C (IN)
8	8
10	10
12	12

Dimensions are in inches

### General Description

- Provides comfortable, effective sensiblecooling to the space.
- Perforated face
- 1/2" Sweat or 1/2" MNPT coil connections
- Quick and simple installation
- Ultra quiet, natural convection driven operation
- Exposed installation

### Basic Unit Configuration

Check  if provided.

Width	Length	Height	Coil Connection	Face Pattern	Finish
<input type="checkbox"/> 13 inches	<input type="checkbox"/> 2 feet <input type="checkbox"/> 7 feet	<input type="checkbox"/> 8 inches	<input type="checkbox"/> 1/2" Sweat Connection	<input type="checkbox"/> Perforated Grille	<input type="checkbox"/> White (WHT)
<input type="checkbox"/> 18 inches	<input type="checkbox"/> 3 feet <input type="checkbox"/> 8 feet	<input type="checkbox"/> 10 inches	<input type="checkbox"/> 1/2" MNPT Connection*		<input type="checkbox"/> Black (BLK)
<input type="checkbox"/> 24 inches	<input type="checkbox"/> 4 feet <input type="checkbox"/> 9 feet	<input type="checkbox"/> 12 inches			
	<input type="checkbox"/> 5 feet <input type="checkbox"/> 10 feet				
	<input type="checkbox"/> 6 feet				

Note:  
 1) MNPT required for CBHK hoses  
 2) CBHK hoses ordered separately

### Accessories

Check  if provided.     Coil Drain