

TMS (FR)

- Model TMS-FR is a UL classified fire rated ceiling diffuser assembly listed in Underwriters Laboratories Fire Resistance Directory. This design meets UL time-vs-temperature test criteria, also NFPA 90A requirements
- For use in three-hour fire rated, exposed grid, suspended ceilings
- All sizes have three cones, giving a uniform appearance where different sizes are used in the same area
- Optional volume damper can be adjusted from the diffuser face without removing the inner cone
- Quick removal of the inner cone with a hex key
- All cones are die-stamped, one-piece construction. Smooth, clean surfaces with no corner joints
- Must be installed in accordance with the installation instructions for UL classification
- Material is heavy-gauge steel
- Non-asbestos thermal insulating blanket



TMS-FR



fire rated

MODEL:

TMS-FR

FINISH:

Standard Finish - #26 White

OVERVIEW

Square / Round Neck / High Performance

Titus fire rated diffusers are UL classified and listed in Underwriters Laboratories Fire Resistance Directory. These diffusers meets UL time vs. temperature test criteria and NFPA 90A requirements.

For Performance Data, please utilize the Square Ceiling diffusers section of the catalog located in Section F. Use Performance Data only for available sizes.

ADVANTAGES

- Delivers supply air in a true 360° pattern. Designed to protect ceilings from streaking and smudging.
- Excellent performance in variable air volume systems. The uniform, nearly horizontal jet from the outer cone maintains effective room air distribution even when the air volume varies over a considerable range.



See website for Specifications

