

Robust Casing Design

Provides superior casing leakage prevention to promote energy efficiency and reduce operating costs.

(Optional) Pre-approved OSHPD seismic certification #0352-10
*factory direct only

EcoShield liner (Optional)

100% recycled, natural fiber insulation that provides superior IAQ and thermal efficiency




Access Door (Optional)

Available on bottom (std) & top for simple enclosure handling changes in the field where bottom access is required

Aerocross sensor

Multi-point center averaging flow sensor provides the most accurate airflow readings in the industry



Hot water coil

AHRI 410 certified coil sized to optimize capacity at lower entering water temperatures

Controls Enclosure

Sized with spacing to fit virtually any controller combination in the industry

Toggle Switch (Optional)

Transformer (Optional)

Titus® Alpha controller (Optional)

BACnet ready, direct digital controls factory installed. Pre-approved OSHPD Seismic Certification

Barrier Plate

Isolates high voltage from low voltage components to meet national and local electrical code requirements

Code & Standard Compliance

NFPA 90A & 90B	ASTM E84	IBC
NFPA 255	ASTM C 1071	NEC
UL 723	ASTM C 739	ASHRAE 62.1
UL 181	ASTM G 21	ASHRAE 130
ASTM C 411	ASTM G 22	AHRI 880

