

CBAL2

Active Linear Chilled Beam

The CBAL2 is offered for both cooling and heating in 24-in width, and lengths from 2 to 10 ft. This unit can be easily integrated into different grid styles within a suspended ceiling or even in drywall ceilings. The low overall height of the CBAL2 product line is ideal for reducing the space required for false ceilings in any application.



FEATURES & BENEFITS

- 24-inch width
- 1-way or 2-way air distribution patterns
- 2 foot to 10 foot lengths, 1 foot increments
- Field reversible coil
- Top, side, or multi-inlet options
- Perforated induced air grille
- Left hand or right hand coil connections
- 2-pipe and 4-pipe coil configurations
- Six nozzle options for capacity optimization
- Hinged induced air grille for roomside coil access
- Commissioning port with roomside access for balancing
- Mounting brackets with adjustments in two directions
- Durable powder coat finish
- ½ sweat water coil connections
- Coil air vent and drain

OPTIONS & ACCESSORIES

- ½" thick foil-faced EcoShield, antimicrobial external insulation
- 12-inch, 18-inch or 24-inch stainless steel braided hoses
- ½" or ¾" MNPT water coil connections
- Constant flow regulators
- Lay-in or tegular border types



dual-function



energy solutions



office spaces



hotels/motels



k-12 education



healthcare



laboratories



universities