



# **Security Barrier Grilles with Sleeve Steel**

Models: MSG-BG-SLV

- Standard 19 mm vertical bars on 152 mm centers with 51 x 6 mm horizontal flat bars on 203 mm centers welded in a 5 mm thick sleeve with 38 x 38 x 3 mm angle frames
- Optional configuration as shown on back





Note: Available in sizes 152 x 152 mm through 2032 x 2032 mm in one piece construction with up to a 305 mm sleeve or 1524 x 1524 mm with larger sleeve lengths. Larger sizes will be shipped in multiple sections for field welding together. Standard sleeve length = 305 mm.

## **General Description**

• TITUS model MSG-BG-SLV is a barrier mounted inside a 5 mm thick sleeve for installation in a wall or other opening as a completed unit. This model effectively maintains security between secured and non-secure areas. Duct connections can be quickly made at both ends. This makes MSG-BG-SLV ideal for installation in security walls.

#### **Construction Detail**

- One angle frame is factory welded in place and one angle frame is shipped loose for field welding in place.
- Optional barrier grille configurations, sleeve gauges and angle frame sizes make this model the most versatile of its kind.
- Optional case hardened bars are hardened to 54-64RC before welding in place.

Standard Finish: #26 White

#### **MSG-BG-SLV Submitted Sizes**

## **Options**

### **Optional Sleeve Gauges**

6 mm thick steel sleeve	
☐ 10 gauge steel sleeve	
☐ Other	

## **Optional Angles Frames**

☐ 38 x 38 x 6
☐ 38 x 38 x 5
25 x 25 x 5
☐ 51 x 51 x 5
☐ 51 x 51 x 6
☐ No Angle Frame
Other

## **Optional Anchor Bar Code**

