

Accessories (Optional)

Check if provided

Optional Factory-Furnished T-Bars

0 No T-Bars
 1 One T-Bar, Inlet Side
 1L One T-Bar, Side Opposite Inlet
 2 Two T-Bars, Outside Edge
 3 All T-Bars
 4 All Center T-Bars, No Outside T-Bars
 5 Two T-Bars, Center & Inlet Side
 5L Two T-Bars, Center & Side Opposite Inlet

Note: Factory supplied outside T-bars are 25 mm wide. Center channels are provided on 2-4 slot units when T-bars are by others.

Optional Slot Diffuser Plaster Frame

PF-TBD

Note: Dimensions are in millimeters.

TBD-30 Diffuser
Ceiling
 25

The PF-TBD slot diffuser mounting frame can be used in sheetrock or plaster ceiling. The frame is mounted in the ceiling by others. The Model TBR-80 is mounted on the inside lip of the frame. Plaster frame is 38 mm high.

Optional Mounting Clips

MTC-1 (One side)
 MTC-2 (Both sides)

6
35
48
Mounting Clips (Two per side)
Inlet

Optional Cross Notch

CN

16
41

Standard Finish: #84 Black on pattern controllers and exposed surfaces
 #26 White on optional T-Bars

General Description

- The Model TBR-80 is designed to return air into the ceiling plenum. Unit includes light shield.
- Outside edge of face has double metal thickness to ensure rigidity and straightness.

- TBR-80 return units are compatible with the TBD-80 series of supply plenum slot diffusers.
- Standard unit for T-bar lay-in. Available for other ceiling systems. Contact your local TITUS Representative.

- Available with 19, 25 and 38 mm slots.
- Number of slots available: 1, 2, 3 and 4.
- Standard lengths: 610, 914, 1219, and 1524.
- Material is steel.



Note: This submittal is meant to demonstrate general dimensions of this product. The drawings on this submittal are not meant to detail every aspect of the product with exactness. Drawings are not to scale. TITUS reserves the right to make changes without written notice.

605 Shiloh Road • Plano, Texas 75074 • 972-212-4800

MPSL-5.0-