

## Grilles and Diffusers • Accessories Aluminum

Model: TRM • TITUS Rapid Mount Frame

$A + 1 \frac{1}{4}''$   
 $* \text{Ceiling Opening} = A + \frac{3}{8}''$   
 Inside Opening =  $A - 1''$

**A = Length of ceiling module**

Dimensions are in inches

1  $\frac{3}{8}''$

Clip is adjustable up and down to fit varying ceiling thicknesses.

1  $\frac{1}{8}''$

3  $\frac{16}{100}''$

1  $\frac{1}{2}''$  to 7  $\frac{8}{100}''$

Frame Detail

Ceiling Module	* Recommended Ceiling Opening	
	B	C
12 x 12	12 1/2	12 1/2
300 x 300mm	313mm	313mm
16 x 16	16 1/2	16 1/2
20 x 20	20 1/2	20 1/2
24 x 12	24 1/2	12 1/2
24 x 24	24 1/2	24 1/2
600 x 600mm	613mm	613mm
36 x 24	36 1/2	24 1/2
48 x 12	48 1/2	12 1/2
48 x 24	48 1/2	24 1/2
60 x 12	60 1/2	12 1/2
60 x 24	60 1/2	24 1/2
72 x 12	72 1/2	12 1/2
72 x 24	72 1/2	24 1/2

(Check actual dimensions before installation.)

Standard Finish: #26 White.

### General Description

- Model TRM TITUS Rapid Mount Frame allows T-bar, lay-in type diffusers (border Type 3) to be installed in surface mounting applications (border Type 1).
- TRM frame is installed in opening and secured in place using security clips. Screws are mounted flush in frame mounting holes.
- Rapid Mount Frame can be mounted in plaster or sheet rock ceiling.
- The TRM can be used to access ceiling plenum. Diffuser with flex connection can be lifted out of frame to access ceiling space.
- Material is aluminum with steel fasteners.