

Submittal


NDR

5-17-16

Plenum Slot Diffusers Nova Series • Down-Blow


Models:


□ N-1-DR • 3/4" Slot • Supply/Return



Accessories (optional)

Check if provided.





The PF-NR diffuser mounting frame can be used in sheetrock or plaster ceiling. The frame is mounted in the ceiling by others. The Model N-1-DR/N-4-DR diffuser is mounted on the inside lip of the frame.

Plaster frame is 1 ½" in height.

Standard Finish: #84 Black

General Description

- TITUS Nova Series supply/return diffusers with blow-down have 3 functions. The first is to project a high induction horizontal air pattern into the room. The second is to deliver a vertical sheet of air along the exterior wall or glass. The third is to return air from the room into the ceiling plenum, with minimal short-circuiting of supply air.
- The down-blow section is located in the center of the diffuser. The horizontal-blow sections are at both sides of the down-blow section.
- The down-blow section is equipped with the TITUS Modulinear pattern controller, which can vary the direction of air flow from vertical to horizontal right or horizontal left. It also controls down-blow air volume.
- Excellent for variable volume applications.
- Designed for both heating and cooling.
- For use in standard lay-in ceiling systems.
- Choice of ¾" or 3/8" supply slot. Return slot is 2" on all models.
- Material is steel.