

## Plenum Slot Diffusers Nova Series • Supply/Return

Models:

- N-1-R • 3/4" Slot • 2" Return
- N-4-R • 3/8" Slot • 2" Return

Model	Inlet Sizes Available	C	F	Nominal Length L
N-1-R	6, 8, 10	3/4	3/4	24, 36, 48,
N-4-R	6, 8, 10	3/8	1 1/4	60

Inlet Size	D	E
6	7 9/16	3
8	10 1/16	4
10	13 1/4	4

Note: 24" length available in 6" and 8" inlets only.

Dimensions are in inches.

### Accessories (optional) Check if provided.


- External Insulation

#### Optional Slot Diffuser Plaster Frame

- PF-NR



Ceiling Opening:  
Length = Nominal Length L plus 1/2"  
Width = Plenum Width plus 3/4"



The PF-NR diffuser mounting frame can be used in sheetrock or plaster ceiling. The Frame is mounted in the ceiling by others. The model N-1-R or N-4-R diffuser is mounted on the inside lip of the frame. Plaster frame is 1 1/2" in height.

## Standard Finish: #84 Black General Description

- TITUS Nova Series high induction N-slot diffusers are excellent for variable volume applications.
- Supply/return diffusers have a return section which allows room air to be returned into the ceiling plenum, with no short-circuiting of supply air.
- Designed for both heating and cooling.
- For use in standard lay-in ceiling systems.
- Choice of 3/4" or 3/8" supply slot, 2" return slot.
- Standard lengths are 24", 36", 48" and 60".
- Material is steel.

This submittal is meant to demonstrate general dimensions of this product. The drawings are not meant to detail every aspect of the product. Drawings are not to scale. Titus reserves the right to make changes without written notice.