


CT-TAF-480, CT-TAF-481, CT-TAF-PP0, CT-TAF-PP3

Access Floor Diffuser Series for use with TAF-HC, TAF-V, and TAF-D Plenums

Perimeter Linear Bar Diffuser • Aluminum • Fixed Bars

CT-TAF-480	• $\frac{1}{4}$ " Spacing	• $\frac{1}{8}$ " Bars	• 0° Deflection
CT-TAF-481	• $\frac{1}{4}$ " Spacing	• $\frac{1}{8}$ " Bars	• 15° Deflection
CT-TAF-PP0	• $\frac{7}{16}$ " Spacing	• $\frac{7}{32}$ " Bars	• 0° Deflection
CT-TAF-PP3	• $\frac{7}{16}$ " Spacing	• $\frac{7}{32}$ " Bars	• 30° Deflection

Diffuser Frame and Core




Type 5 heavy duty mounting frame is shown.

CT-TAF diffusers are designed to fit the dimensions of the TAF-HC, TAF-V, and TAF-D plenums. See TAF-HC, TAF-V, and TAF-D submittals for information on required hole size for access floor tile.

	Dim 1 Length	Dim 2 Width
Single-Piece Core	15 $\frac{3}{4}$ "	7 $\frac{3}{4}$ "
Multi-Piece Core	15 $\frac{1}{2}$ "	7 $\frac{3}{4}$ "

Removable core is furnished with frame. See below for core selections.



$\frac{1}{4}$ " Spacing	$\frac{7}{16}$ " Spacing
$\frac{1}{8}$ " Bars	$\frac{7}{32}$ " Bars
<input type="checkbox"/> Model CT-TAF-480 • 0° Deflection 	<input type="checkbox"/> Model CT-TAF-PP0 • 0° Deflection
<input type="checkbox"/> Model CT-TAF-481 • 15° Deflection 	<input type="checkbox"/> Model CT-TAF-PP3 • 30° Deflection

Note:

† Not recommended for floor applications with heavy loads or high traffic.

If placing furniture on cores, furniture legs should be a minimum of core spacing plus two bars wide to avoid placing a horizontal load on core.

General Description

- Titus CT-TAF diffusers are fixed linear bar diffuser for underfloor applications.
- The CT-TAF is designed to be integrated with the TAF-HC, TAF-V, and TAF-D plenums (see TAF-HC, TAF-V, and TAF-D submittals for more information).
- CT-TAF frame drops into plenum opening and sits on top of carpeting.
- All deflection bars are fixed and are parallel to the long dimension.
- Fixed Bars are extruded aluminum.
- Standard finish is #26 white.