

T<sub>3</sub>SQ MAXIMUM FLOW SELECTION

Inlet Size	Neck Velocity Velocity Pressure	400 0.010	500 0.016	600 0.022	700 0.031	800 0.040	900 0.050	1000 0.062
6"	Static pressure	0.016	0.024	0.037	0.048	0.064	0.082	0.100
	Total Pressure	0.026	0.040	0.059	0.079	0.104	0.132	0.162
	cfm	79	98	118	137	157	177	196
	NC	5	10	14	17	20	23	25
	Throw, ft	1-2-3	1-2-4	2-3-5	2-3-6	2-3-7	3-4-7	3-4-8
8"	Static pressure	0.021	0.032	0.047	0.063	0.083	0.106	0.130
	Total Pressure	0.031	0.048	0.069	0.094	0.123	0.156	0.192
	cfm	140	175	209	244	279	314	349
	NC	8	13	17	20	23	25	28
	Throw, ft	2-3-5	2-3-7	2-4-8	3-5-9	3-5-10	4-6-10	4-7-11
10"	Static pressure	0.030	0.047	0.069	0.093	0.122	0.155	0.190
	Total Pressure	0.040	0.063	0.091	0.124	0.162	0.205	0.252
	cfm	218	273	327	382	436	491	545
	NC	14	19	23	26	29	31	34
	Throw, ft	3-4-8	4-5-10	4-6-11	5-8-12	6-9-13	6-10-14	7-10-14
12"	Static pressure	0.048	0.075	0.109	0.147	0.192	0.244	0.301
	Total Pressure	0.058	0.091	0.131	0.178	0.232	0.294	0.363
	cfm	314	393	471	550	628	707	785
	NC	24	29	33	36	39	41	44
	Throw, ft	4-6-11	5-8-12	6-9-13	7-10-14	8-11-15	9-11-16	10-12-17

AIR DISTRIBUTION AT VARIOUS DAMPER POSITIONS

The performance of the T<sub>3</sub>SQ diffuser is related to supply static pressure and size. If the supply static pressure is held at a constant value and the VAV diffuser damper is throttled to a closed position, the airflow pattern is changed from a square pattern to a star pattern. The isovel in the adjacent illustration demonstrates this pattern change. With the reduction of cfm, throw does not decrease as in standard diffusers. As the damper closes the discharge velocity is slightly increased, minimizing throw reduction. With a fixed inlet pressure, the sound values have very small changes of intensity as the damper is modulated.

